LT2-B847Mark II

Twin Needle Drop Feed Lock Stitcher Twin Needle Drop Feed Lock Stitcher with Thread Trimmer



Specifications

_		-1
Application		For thin materials
Max. speed		4,000 rpm
Maxstitch length		4mm
Needle bar stroke		33.4 mm
Threadtake-up stroke		49.9 mm
Height of	Presser bar lifter	7 mm
presser foot	Knee lifter	13 mm (With thread wiper:10 mm)
Height of feed dog		1 mm
Needle		DP×5#9-#14
Hook		Horizontal rotary hook (vertical axis)

	-400
Thread trimmer	Scissors type (Solenoid)
Thread wiper	Solenoid type
Quick reverse	Solenoid type

B847 Mark II (For Standard)

For normal


*In case of using over 1–1 / 2" (38.1 mm) gauge parts, it is necessary to make special machining on the arm-bed.

The specification with a maximum stitch width of 77 mm is available.

Please consult your Brother representative concerning delivery date and price.

*The O symbol is a presser foot assembly with finger guard.

Needle	Needle gauge Needle clamp		, , ,		Feed dog		Presser foot assy		
		assy							
			(–1)		(–1)		(–1)		
			For light materials	Fornewsynthetic	_	For new synthetic	For light	Fornew	
(inch)	(mm)		1 Orlight Haterials	fiber	materials	fiber	materials	synthetic fiber	
1/8	(3.2)	158794–101	S07686-001		S07696-001		S07393-001		
170	(0.2)	100704 101	007000 001		007000 001		S38544-001 O		
3/16	(4.8)	158791–101	S07688-001	S36842-001	S07698-001	S36838-001	S07395-001	S36839-001	
3/10	(-1.0)	130731-101	307000-001	0000-12-001	307030-001	330000-001	S38542-001 O	330039-001	
1/4	(6.4)	158792–101	S07689-001	S36841-001	S07699-001	S36835-001	S07397-001	S36836-001	
17-	(0.4)	100/02 101	007000 001	COCC+1 001	007000 001	C00000 001	S38543-001 ^O	555550-001	
1/2	(12.7)	158797–101	S07693-001		S07703-001		S07684-101 O		
3/4	(19.1)	158806-101	S07996-001		S07998-001		S07889-101 O		
	20mm	S00937-001	S13479-001		S07998-001		S13480-101 O		
7/8	(22.2)	158807-101	S07997-001	S37011-001	S07999-001	S07999-001	S07894-101 O	S37012-001	




B847 Mark II (For Standard)

For shirt fronts

*The O symbol is a presser foot assembly with finger guard.

Needle gauge	Needle clamp assy	Needle plate	Feed dog	Presser foot assy
		(–1)	(–1)	(–1)
mm		For light materials	For light materials	For light materials
18mm	S14352-001	S14354-001	S14357-001	S14355-101 O
20mm	S00937-001	S13479-001	S14360-001	S14358-101 O
22mm	158807–001	S07997-001	S14363-001	S14361−101 O
24mm	S14364-001	S14366-001	S14369-001	S14367-101 O
26mm	S14370-001	S14372-001	S14375-001	S14373-101 O
28mm	S14376-001	S14378-001	S14381-001	S14379-101 O
30mm	S16651-001	S16653-001	S16656-001	S16654-101 O



B847 Mark II (For Thread trimmer)

For normal

*The thread trimming fixed knife (part No. S07527–001) and the installation screw (part No. 148539–101) are not provided with the needle plate, so they must be ordered separately if required.

*In case of using over 1-1/2" (38.1 mm) gauge parts, it is necessary to make special machining on the arm-bed.

The specification with a maximum stitch width of 77 mm is available.

Please consult your Brother representative concerning delivery date and price.

*The O symbol is a presser foot assembly with finger guard.

Needle gauge Needle clamp		Needle plate		Feed dog		Presser foot assy		
		assy						
(inch)	(mm)		(-1) For light materials	Fornewsynthetic fiber	(–1) For light materials	For new synthetic fiber	(-1) For light materials	For new synthetic fiber
1/8	(3.2)	158794–101	S07401-001		S07409-001		S07393-001	
1/0	1/6 (3.2) 136	150794-101	50/401-001		507409-001		S38544-001 O	
3/16	(4.0)	450704 404	C07402 004	C2C044 004	C07440 004	S36843-001	S07395-001	S36839-001
3/16	(4.8)	158791–101	S07403-001	S36844-001	S07410-001		S38542-001 O	
1 / 1	(C 4)	158792–101	S07405-001	S36847-001	S07411-001	S36846-001	S07397-001	S36836-001
1/4	1/4 (6.4)	130/92-101	30/400-001	330047-001	30/411-001	3300 1 0-001	S38543-001 O	330030-001
5/16	(7.9)	158793-101	S07676-001		S07680-001		S07682-001	
3/8	(9.5)	158798–101	S13621-001		S13623-001		S13624-001	
1/2	(12.7)	158797–101	S07678-001		S07681-001		S07684-101 O	
3/4	(19.1)	158806-101	S07886-001		S07888-001		S07889-101 O	
7/8	(22.2)	158807–101	S07891-001	S37014-001	S07893-001	S07893-001	S07894-101 O	S37012-001
1	(25.4)	158805–101	S15088-001		S15090-001	·	S15091-101 O	
1–1/4	(38.1)	158799-001	S20914-001		S20916-001		S20917-101 O	

