

SB-7270

SB-7280

Single Needle Top and Bottom Feed Lock
Stitcher with Large Hook

Single Needle Top and Bottom Feed Lock
Stitcher with Large Hook and Thread
Trimmer



Specifications

Model	SB-7270	SB-7280
Use	Heavy materials	
Max. sewing speed	2,000 rpm	
Max. stitch length	8 mm	
Needle bar stroke	37 mm	
Height of presser foot	Manual : 6.5 mm Knee : 16 mm	
Height of feed dog	1.2 mm	
Needle	DP × 17 #23	
Thread trimmer		○ (Solenoid)
Quick reverse		○ (Solenoid)

GAUGE PARTS LIST

Standard gauge

[SB-7270]

Needle plate	Feed dog	Standard feet		
		Walking foot	Presser foot	Presser foot assy, w/FG
<p>ϕ 2.5 R 1 T 2.6</p> <p>10.0, 10.8, 2.5, 5.5, 26.5, 14.5, 3.2, 4.6</p> <p>SW0057-001</p>	<p>P 1.6 H 6.6</p> <p>27.5, 18.5, 10.5, 9.6, 11.1, 3.5, 14.5, 3.8</p> <p>SW0120-001</p>	<p>SW0216-001</p>	<p>SW0083-001</p>	<p>SW0105-001</p>

Standard gauge

[SB-7280]

Needle plate	Feed dog	Standard feet		
		Walking foot	Presser foot	Presser foot assy, w/FG
<p>ϕ 2.6 R 1(溝) T 2.8</p> <p>9.5, 10.6, 2.5, 8, 23, 16, 3.2, 4.6</p> <p>147322-101</p>	<p>P 1.6 H 6.7</p> <p>27, 19, 8, 9, 11.2, 3.5, 14.7, 4</p> <p>S06629-001</p>	<p>SW0216-001</p>	<p>SW0083-001</p>	<p>SW0105-001</p>

Option gauge

Feet for piping		Narrow type feet for small parts		Reverse feet		
Walking foot	Presser foot	Walking foot	Presser foot	Walking foot	Presser foot	Presser foot assy, R-w/FG
<p>151847-001: 6.4 mm (1/4) 151848-001: 7.9 mm (5/16) 151849-001: 9.5 mm (3/8)</p>	<p>151850-001</p>	<p>151851-001</p>	<p>151852-001</p>	<p>S04501-001</p>	<p>S04502-101</p>	<p>S36917-001</p>